




Push Button Sensor 2, 3-gang 24 V zero-voltage with inscription space



| Specification | Order No. | Packing unit | PS | EAN |
|---|-----------|--------------|----|---------------|
|  Stainless Steel (lacquered) | 2003 20 | 1 | 02 | 4010337050544 |
|  Aluminium (lacquered) | 2003 203 | 1 | 02 | 4010337050520 |
|  Clear + pure white glossy | 2003 100 | 1 | 02 | 4010337047971 |

Features

Push button sensor 2 for connection to 24 V control systems

- Three rockers with two red LEDs each for status display.
- Safeguarded from disassembly because it is screw-fastened.
- Backlighting.
- Connection of six push buttons, six LEDs, and backlighting via the terminal block on the rear.

Technical data

| | |
|------------------------------------|-----------------|
| Rated voltage of each push button: | AC/DC 24 V SELV |
| Load capacity of each push button: | max. 20 mA |
| Rated voltage of each LED: | DC 24 V SELV |
| Load capacity of each LED: | 1 mA |
| Connection | |
| - terminal block: | 2 x 9-pole |
| Connections | |
| - single-wire: | Ø max. 0.8 mm |
| Ambient temperature: | -5 °C to +45 °C |

Illustrations are similar and may deviate from originals.

Notes

- Suitable for SELV circuits only.
- Can also be connected with illumination.
- Professional labelling with the Gira Inscription Service www.marking.gira.com.

Scope of supply

-
